

संशोधित अल्पकालीन निविदा

संस्थान पुस्तकालय भवन में Department of Ayurveda Manuscriptology के कक्षा संख्या 302 की म्यूजियम के 04 बुडन बुक शॉकेस को रिपयेर एवं बुडन पॉलिश व कक्षा संख्या 301 नॉडल ऑफिसर चैम्बर के लिए Ayurveda Manuscriptology का Logo बनाये जाने हेतु अल्पकालीन निविदा पत्रांक 7487 दिनांक 23.08.2024 के तहत दिनांक 27.08.2024 तक निविदाएं मांगी गई थी, जिसको संशोधित करते पुनः उक्त कार्य की निविदा दिनांक 21.10.2023 तक मांगी जाती है। इच्छुक फर्म साईट का निरीक्षण कर अपनी निविदाएं दिनांक 21.10.2024 को मध्याह्न 3:00 बजे तक सीलबन्ध लिफाफे पर उक्त निविदा का नाम लिखकर संस्थान में कुलपति महोदय को प्रेषित करें। कार्य का विवरण निम्नप्रकार है :-

S.N	Work Description	Qty.	Rate per unit	Amount
1.	Providing & fixing storage unit/over head unit/side unit/back unit at all floors of depth 450 mm approx of required size: (a) The carcass made of 18mm thick commercial board sides/front/shelves skirting/bottom & top and back with 12 mm thick commercial board.shelves to be provided at height of 300 to 400 mm as per the direction of EIC. (b) All outer surface (except back side) finished with 1.0 mm thick decorative/coloured laminate. (c) Balancing laminate (0.65 mm) on all inside surfaces. (d) 20x6 mm teak wood lipping, locking arrangement on all shutters, magnetic catcher (one on each shutter) handles (100 mm long with S.S. harline Finish-one on each shutter) auto closing hinge, towerbolts, SS shelf pin all complete as per the direction and satisfaction of Engineer-in-charge. The areas not having laminate shall be finished with polish (for payment purpose front area to be measured)	2.50 Sqm		
2.	Providing and fixing internal wall panels on Light gauge steel frame work with 12.5mm thick gypsum plaster board conforming IS 2095:2011 fixed on cement board as per standard sizes fixed with self-drilling / tapping screws / fasteners @ 60cm c/c of approved make, Screws shall be of counter sunk rib head of 1.60mm to 4 mm thick or 8 to 10 gauge of length varying from 25 to 45 mm. Proper taping and jointing to be done using fiber mesh tape and epoxy and acrylic based jointing compound for seamless finish.(cost of frame work to be paid for separately. Cement Bonded particle board 8 mm (Termite, Fire & Moisture Resistance), as per IS:14276 : 1995	6.50 Sqm		
3.	Polishing in high gloss/matt finish melamine clear polish on wood work in required color/wooden shade texture with following process in the sequence as detailed below: 1. The surface to be polished is rubbed with sand paper 80/ 120 no. and then with sand paper of 160/180 nos. 2. Applying two coats of sealer with spray gun and allowing sufficient drying time for 1st coat and 2nd coat is allowed to dry for 8 to 12 hrs. 3. On drying of sealer coat, wet rubbing with emery cloth of finer grading with ample water to remove excess sealer layer and make the surface further smooth after this wet rubbing, then surface is applied with special grade melamine fillers to fill all the small and big holes/grooves etc. Filler coat to be allowed to dry for 4 to 6 hrs on which again a light wet rubbing is done this surface is further allowed to dry for 12 hrs. 4. On this, 1st coat of melamine polish is applied with spray gun using melamine clear polish and melamine thinner in required proportion. This 1st coat is allowed to dry for 24 hrs then this dry surface is again fine wet rubbed smooth, which is further allowed to dry for 12 hrs. The final melamine polish is applied with compressor pressure spray gun using melamine clear polish and melamine thinner mixed in required proportion complete as per direction of Engineer-in-Charge. (Final coat to be done in 1 or 2 layers without gap of time.)	60 Sqm		
4.	Providing and fixing cup board shutters with 25 mm thick veneered particle board IS : 3097 marked, exterior grade (Grade I), of approved make, including IIInd class teak wood lipping of 25 mm wide x 12 mm thick with necessary screws and bright finished stainless steel piano hinges, complete as per direction of Engineer-in-Charge. 9.130.1 With decorative veneering on one side and commercial veneering on other side 25 MM thick.	05 Sqm		
5.	Providing and fixing bright finished brass butt hinges with necessary screws etc. complete : 125x85x5.5 mm (heavy type)	05 Each		
6.	Float glass panes 4 mm thick glass pane (weight not less than 10kg/sqm). sqm	06 Sqm		
7.	Providing and fixing 35 mm thick factory made laminated veneer lumber door shutter conforming to IS : 14616 and TADS 15:2001 (Part B), fixing with butt hinges of required size with necessary screws, all complete as per directions of Engineer- in-charge and panelling with panels of : (Note:- Butt hinges and necessary screws shall be paid separately) 12 mm thick pre-laminated particle board (decorative lamination on both sides) grade -I, medium density flat pressed, three layer particle board FPT- I or graded wood particle board FPT- I, conforming to IS : 3087, bonded with BWP type synthetic resin adhesive as per IS : 848 and pre laminated conforming to IS : 12823, Grade I, Type - II marked :	10 Sqm		
8.	Providing and fixing of external wall system on Light gauge steel frame work with outer face cement boards as per standard sizes fixed with self- drilling / tapping screws / fasteners @ 60cm c/c of approved make. A groove of 2 mm to 3mm shall be maintained and grooves shall be sealed with silicon based sealant. The board shall be fixed in a staggered pattern. Screws shall be of counter sunk rib head of 1.60mm to 4 mm thick or 8 to 10 gauge of length varying from 25 to 45 mm and. Internal face 12.5 mm thick gypsum plaster board fixed on cement board as per standard sizes fixed with self drilling / tapping screws / fasteners @ 60cm c/c of approved make, proper taping and jointing to be done using fiber mesh tape and epoxy and acrylic based jointing compound for seamless finish.(cost of frame work to be paid for separately) Outer face: Outer face having 6mm thick fiber cement board fixed on 9mm thick fiber cement board, Type A, as per IS:14862:2000 (high pressure steam cured) Inner Face :- 12.5 mm thick gypsum plaster board conforming to IS 2095:2011 fixed on 8 mm thick fibre cement board confirming to IS:14862:2000 of type B (High pressure steam cured)	15 Sqm		
	Total Rupees			
	GST			

1. फर्म को कार्य का भुगतान कार्य सन्तोषप्रद होने पर किया जायेगा।
2. फर्म को उपरोक्त विवरणानुसार ही कोटेशन भर कर प्रस्तुत करना होगा।
3. फर्म द्वारा कोटेशन के साथ GST का प्रमाण पत्र संलग्न करना अनिवार्य है।
4. कार्य पूर्ण होने पर विल 02 प्रतियों में सम्पदा विभाग में प्रस्तुत करना होगा जिससे भुगतान की कार्यवाही की जा सके।
5. पूर्व में प्रस्तुत किए गए कोटेशन मान्य नहीं होंगे तथा समय सीमा उपरान्त प्राप्त कोटेशन पर कोई विचार नहीं किया जावेगा।

उप निदेशक (प्रशासन)

प्रतिलिपि:- सूचनार्थ हेतु प्रेषित।

01. प्रतिष्ठापन शाखा (रिसिप्ट) को दी जाकर लेख है दिनांक 21.10.2024 को मध्याह्न 03:00 बजे तक उक्त कार्य की निविदा प्राप्त कर सम्पदा विभाग में भिजवाये जाने की व्यवस्था करावें।

उप निदेशक (प्रशासन)